



## Drive-Away Antenna



### Features

- 1.2m and 1.5m Reflector options
- Compact and Robust
- Auto-Pointing IPOINT™ Controller
- Can be Operated by Anyone
- Acquires in < 3 minutes
- Available with integrated Tx Power up to 125W Ku-Band 1:1 redundant system
- Simple Operation – Requires no Satellite Communication Expertise
- Acquires the satellite within minutes
- Completely automatic one button acquisition of required satellite
- Low cost, high performance and reliable satellite acquisition
- Ultra-Compact
- Aerodynamic Antenna Enclosure

The PIONEER120™ & PIONEER150™ antennas are ultra-compact roof mounted systems. The antennas encompass the drive control, positioning hardware and BUC into the aerodynamic antenna enclosure, making the system a robust standalone sub-assembly ready to install onto almost any vehicle. The versatile power-payload of the PIONEER Class antennas has been designed to house SSPAs with power levels up to 100W Ku-Band or Extended Ku-Band in single thread or 1:1 redundant configurations.

The system is simple to install, set up and use. Following relocation of the antenna, the system will reliably and accurately locate and lock on to the designated traffic satellite rapidly within minutes. The IPOINT™ Auto Acquisition Controller uses industry standard position transducers and a sophisticated pattern recognition algorithm to confirm and refine its heading information using visible satellites. The controller is mounted on the antenna structure with a separate control panel with integral power supply in a rack mount unit for mounting within the equipment area.



## IPOINT™ specifications

Operational modes	Auto-acquire      Unstow      Stow      Configure
LNB Power supply	Can provide 13/18VDC switchable at up to 600mA on RF cable to power LNB and diseq tones.
RF Signal Input	L-band signal from LNB Level -70 to -20 dBm
Display	2 line LCD display giving Mode, Signal Level Indication and Position Information
Motor Drive	Can drive all motors at 24VDC up to 12A. Pulse width modulation from 10% to 100%.
Limit Switches	Stow Azimuth and Elevation switches

## Options

Hand Held Controller	Hand Held Controller with LCD display
----------------------	---------------------------------------

## Physical

Temperature	-20°C to 55°C - Operating
Range	-30°C to 85°C - Non Operating (storage)
Humidity	5% to 95% RH non condensing - Operating 0% to 99% RH non condensing - Non Operating (storage)
Altitude	10,000 feet max
Input Power	110 or 230V, single phase, 50/60Hz, 500W
Dimensions	Antenna mounted controller 10.8" (275mm) x 10.3" (262mm) x 2.7" (69mm) Rack mounted Control panel containing PSU: 19" (483mm) x 1.75" (44mm) x 16" (406mm)
Mounting	Antenna mounted controller: Antenna specific mounting brackets Rack mounted Control panel containing PSU: Standard 1U rack mount

## Standards

Designed to meet	EN55022 and EN50082-1
------------------	-----------------------



## Physical

	PIONEER120™	PIONEER150™
Antenna Width	123cm	150cm
Antenna Height	127cm	152cm
Geometry	Offset, dual optic	Single Offset
Reflector Material	SMC	Carbon Fibre
Weight	100kg	100kg
<b>Range</b>		
Azimuth	+/-185°	+/-185°
Elevation	10-90°	10-90°
Polarization	+/-95°	+/-95°
Feed Interface	WR75	WR75

## Electrical

### Receive

Controller	IPOINT™	IPOINT™
Polarization	Linear	Linear
Frequency Band	10.7-12.75 GHz	10.7-12.75 GHz
Gain @12.5GHz	41.8 dBi	43 dB;
G/T(30° elevation)@12.5GHz	21dBK	23 dBK

### Transmit

Polarization	Linear Orthogonal	Linear Orthogonal
Frequency Band	13.75-14.5 GHz	13.75-14.5 GHz
Gain @14.25GHz	43 dBi	44.7 dB;
VSWR	1.3:1	1.3:1
Isolation RX/TX (13.75-14.5 GHz)	40dB	40dB
Isolation TX/RX (10.75-12.75 GHz)	75dB	75dB

## Wind Speed

Operational up to 45 mph (72 kph)  
Survival up to 100 mph stowed (161 kph)



# Advantech

wireless broadband culture

## **NORTH AMERICA**

### *USA*

2325 Dulles Corner Boulevard  
Suite 500, Herndon  
VA 20171 USA  
Tel: +1 703 788-6882  
Fax: +1 703 788-6511  
info.usa@advantechwireless.com

### *CANADA*

2341 Alfred-Nobel  
Montreal, QC  
Canada H4S 2B8  
Tel: +1 514 335-3550  
Fax: +1 514 335-3022  
info.canada@advantechwireless.com

657 Orly Avenue  
Montreal, QC  
Canada H9P 1G1  
Tel: +1 514 420-0045  
Fax: +1 514 420-0073  
info.canada@advantechwireless.com

550 Campbell Drive  
Cornwall, ON  
Canada K6H 6T7  
Tel: +1 613 936-2000  
Fax: +1 613 936-2010  
info.canada@advantechwireless.com

## **EUROPE**

### *UNITED KINGDOM*

39 Edison Road  
St.Ives Huntingdon, Cambridgeshire  
United Kingdom PE27 3LF  
Tel: +44 1480 357 600  
Fax: +44 1480 357 601  
info.uk@advantechwireless.com

### *SWEDEN*

Fabriksgatan 7  
SE-412 50, Göteborg  
Sweden  
Tel: +46 31 771 79 00  
Fax: +46 31 771 79 10  
info.sweden@advantechwireless.com

### *RUSSIA & CIS*

107564, Moscow  
Krasnobogatirskaya  
2-2, 2 floor, office #5  
Tel: +7 495 967 1859  
Fax: +7 495 967 30 24  
info.russia@advantechwireless.com

## **SOUTH AMERICA**

### *BRAZIL*

Avenida Rouxinol, 55, 8 andar, sala  
04516-000, Moema, São Paulo, SP, Brasil  
Tel: +55 11 3054 5701  
Fax: +55 11 5041 4026  
info.brazil@advantechwireless.com

### *ARGENTINA*

Bogado 16 - Of. 2  
B1609IEB - San Isidro  
Buenos Aires - Argentina  
Tel: +5411 4731 1034  
Cel: +54 911 4492 5601  
info.argentina@advantechwireless.com